

## Operable solutions – Concealed Transfer

The View Concealed Transfer provides power and control to a door or window unit that contains View Dynamic Glass. The Concealed Transfer installs in the door/window jamb, and connects the IGU cable from the Window Controller (which sits outside the door/window frame) to the IGU in the window or door glazing.

### Features:

- Provides a concealed wire pathway for the IGU cable when mortised into the door/window frame. Typically installed above the second hinge in a door (figs. 1 and 2).
- Tamper resistant—no exposed openings prevents foreign objects from reaching wires or jamming the device.
- Two standard finishes available: aluminum and oil rubbed bronze.
- All metal construction.
- Uses industry standard Power Transfer unit, modified for View-specific installation.
- Tested to 1 million cycles.
- Comes with the IGU cable pre-installed and pre-terminated.
- Maintains View standard BoS warranty when used in the Dynamic Glass system.

### Usage:

- 1- $\frac{3}{4}$ " min door/window thickness
- 0-180 deg opening with up to a 5" butt hinge
- 0-180 deg opening with up to a  $\frac{3}{4}$ " offset pivot
- 0-130 deg opening with 5- $\frac{1}{2}$ " butt hinge
- 0-110 deg opening with 6" butt hinge
- Will not function on center-hung or balanced doors

### Warranty

All cables and components carry a warranty for a period of 5 years from date of delivery by View. Refer to standard warranty terms and conditions for more details.

### Models available

1. VP-CT-AL-000  
Concealed Transfer aluminum

2. VP-CT-BZ-000  
Concealed Transfer oil rubbed bronze





fig. 1



fig. 2



*Data subject to change. See View Concealed Transfer Installation Guide for further details on dimensions and installation.*

### Project submittal information

JOB NAME:	NOTES:
JOB NUMBER:	